



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG9

G-Drink 9 Vendo Legend®

	DG9
ABMESSUNGEN H x B x T (mm)	1830* x 1220 x 845
NETTOGEWICHT (Standard-Gerät ohne Optionen)	345 kg
AUSWAHLEN PRO ETAGE	9
ANZAHL ETAGEN	Standard 5 / max. 7
AUSWAHLEN GESAMT	Standard 45 / max. 63
MAX. KAPAZITÄT (0,33 ltr. DOSEN)	504
MAX. KAPAZITÄT (0,50 ltr. PET FLASCHEN)	360
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+2°C bis +10°C
KÜHLAGGREGAT	HCD
ELEKTROANSCHLUSS	230/240 V - 50/60 Hz
MAX. LEISTUNGS-AUFNAHME	370 W
ENERGIEKLASSE	TBC
ENERGIEVERBRAUCH - kWh/annum	TBC

*Mit Nivellierschrauben



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG6

G-Drink 6 Vendo Legend®

	DG6
ABMESSUNGEN H x B x T (mm)	1830*x 945 x 845
NETTOGEWICHT (Standard-Gerät ohne Optionen)	295 kg
AUSWAHLEN PRO ETAGE	6
ANZAHL ETAGEN	Standard 5 / max. 7
AUSWAHLEN GESAMT	Standard 30 / max. 42
MAX. KAPAZITÄT (0,33 ltr. DOSEN)	336
MAX. KAPAZITÄT (0,50 ltr. PET FLASCHEN)	240
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+2°C bis +10°C
KÜHLAGGREGAT	HCD
ELEKTROANSCHLUSS	230/240 V - 50/60 Hz
MAX. LEISTUNGS-AUFNAHME	370 W
ENERGIEKLASSE	TBC
ENERGIEVERBRAUCH - kWh/annum	TBC

*Mit Nivellierschrauben