



Ready to serve 24 hours  
a day

THE SANDENVENDO COLD DRINKS  
VENDING MACHINES - Easy programming  
using selection button sequence -  
Electronic control and data-recording -  
Energy Management by real time clock -  
Each column driven via individual vend  
motor - 24 V DC motors - Interchangeable  
parts - Quadruple loading for 0.33 l cans  
and double loading for 0.50 l PET bottles up  
to 245 mm height

SVE 480-7 DD

## NarrowStack Basic 480-7 DD

### TECHNICAL SPECIFICATIONS

	SVE 480-7 DD
DIMENSIONS H x W x D (mm)	1830 x 750 x 950
WEIGHT (NET - Standar machine without options)	295 Kg
NO. OF SELECTIONS / COLUMNS	7 / 7
MAX. CAPACITY (0.33 l CANS)	476
MAX. CAPACITY (0.50 l PET BOTTLES)	238
MAX. PRODUCT LENGTH (mm)	505
MAX. PRODUCT DIAMETER (mm)	72
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Thermostat
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	500 W
POWER SUPPLY	230 V / 50 Hz

### OPTIONAL

CUSTOMIZED CABINET & DOOR COLOUR  
2 LINE LCD DISPLAY  
SECURITY CASH BOX SYSTEM  
SAFETY SLIDE COIN INSERT  
WALL/FLOOR FIXING KIT  
SPECIAL CODED LOCK (RIELDA)  
BRANDING  
OUTDOOR KIT IP34  
STACK ASSEMBLY FOR PRODUCT Ø 74 mm  
LOADING RACK



SVE 550-8 DD

Ready to serve 24 hours a day

THE SANDENVENDO COLD DRINKS VENDING MACHINES - Easy programming using selection button sequence - Electronic control and data-recording - Energy Management by real time clock - Each column driven via individual vend motor - 24 V DC motors - Interchangeable parts - Quadruple loading for 0.33 l cans and double loading for 0.50 l PET bottles up to 245 mm height

## NarrowStack Basic 550-8 DD

### TECHNICAL SPECIFICATIONS

### SVE 550-8 DD

DIMENSIONS H x W x D (mm)	1830 x 850 x 940
WEIGHT (NET - Standar machine without options)	335 Kg
NO. OF SELECTIONS / COLUMNS	8 / 8
MAX. CAPACITY (0.33 l CANS)	544
MAX. CAPACITY (0.50 l PET BOTTLES)	272
MAX. PRODUCT LENGTH (mm)	505
MAX. PRODUCT DIAMETER (mm)	72
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Thermostat
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	500 W
POWER SUPPLY	230 V / 50 Hz

### OPTIONAL

- CUSTOMIZED CABINET & DOOR COLOUR
- 2 LINE LCD DISPLAY
- SECURITY CASH BOX SYSTEM
- SAFETY SLIDE COIN INSERT
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- BRANDING
- OUTDOOR KIT IP34
- STACK ASSEMBLY FOR PRODUCT Ø 74 mm
- LOADING RACK



Ready to serve 24 hours a day

THE SANDENVENDO COLD DRINKS VENDING MACHINES - Easy programming using selection button sequence - Electronic control and data-recording - Energy Management by real time clock - Each column driven via individual vend motor - 24 V DC motors - Interchangeable parts - Quadruple loading for 0.33 l cans and double loading for 0.50 l PET bottles up to 245 mm height

SVE 680-10 DD

## NarrowStack 680-10 DD

### TECHNICAL SPECIFICATIONS

### SVE 680-10 DD

DIMENSIONS H x W x D (mm)	1830 x 1010 x 950
WEIGHT (NET - Standar machine without options)	370 Kg
NO. OF SELECTIONS / COLUMNS	10 / 10
MAX. CAPACITY (0.33 l CANS)	680
MAX. CAPACITY (0.50 l PET BOTTLES)	340
MAX. PRODUCT LENGTH (mm)	505
MAX. PRODUCT DIAMETER (mm)	72
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	1000 W
POWER SUPPLY	230 V / 50 Hz

### OPTIONAL

- CUSTOMIZED CABINET & DOOR COLOUR
- 2 LINE LCD DISPLAY
- SECURITY CASH BOX SYSTEM
- SAFETY SLIDE COIN INSERT
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- BRANDING
- OUTDOOR KIT IP34
- STACK ASSEMBLY FOR PRODUCT Ø 74 mm