



Something new,
something different.

SandenVendo carefully observed the behaviour of coffee machines, studied optimization of the energy consumption and identified the root causes of chronic problems.

The challenge to create a trouble-free machine is, to say the least, big and can only be accomplished by looking at the design from a different perspective.

TSC

CaffèUNO "PRO" Espresso

TECHNICAL SPECIFICATIONS	TSC
DIMENSIONS H x W x D (mm)	770 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	2.4 kg (hopper)
POWDER CANISTER	2 Large 1 Small
GRINDER	professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50 /60 Hz
ENERGY CONSUMPTION*	134 Wh/L

*Energy consumption in Wh per liter of Espresso dispensed



Something new, something different.

SandenVendo carefully observed the behaviour of coffee machines, studied optimization of the energy consumption and identified the root causes of chronic problems.

The challenge to create a trouble-free machine is, to say the least, big and can only be accomplished by looking at the design from a different perspective.

TSE

CaffèUNO - Espresso

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	TSE
DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	1.2 kg
POWDER CANISTER	2 Large 1 Small
GRINDER	professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50 /60 Hz
ENERGY CONSUMPTION*	134 Wh/L

*Energy consumption in Wh per liter of Espresso dispensed

OPTIONAL

- TOUCH SCREEN 10" MULTI-LANGUAGE
- LARGE ESPRESSO BREWER
- SPECIAL CODED LOCK (RIELDA)
- CUP SENSOR
- EXTERNAL WATER TANK KIT (20 l)
- WATER SOFTNER (FILTER)
- CUSTOMIZED CABINET COLOUR
- BASE CABINET
- VALIDATOR KIT



Something new, something different.

SandenVendo carefully observed the behaviour of coffee machines, studied optimization of the energy consumption and identified the root causes of chronic problems.

The challenge to create a trouble-free machine is, to say the least, big and can only be accomplished by looking at the design from a different perspective.

TSH

CaffèUNO - Instant

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	TSH
DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
POWDER CANISTER	2 Large 2 Medium 1 Small
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50 /60 Hz
ENERGY CONSUMPTION*	134 Wh/L

*Energy consumption in Wh per liter of Espresso dispensed

OPTIONAL

- TOUCH SCREEN 10" MULTI-LANGUAGE
- SPECIAL CODED LOCK (RIELDA)
- CUP SENSOR
- EXTERNAL WATER TANK KIT (20 l)
- WATER SOFTNER (FILTER)
- CUSTOMIZED CABINET COLOUR
- BASE CABINET
- VALIDATOR KIT