



Uniqueness at a glimpse

Enjoy an authentic Italian espresso: G-Caffè. UNI-Q is the freestanding coffee vending machine that extracts all the essence of coffee to its utmost flavour thanks to its ingeniously designed espresso brewer.

Equipped with an innovative temperature management system with an instant heater, G-Caffè. UNI-Q is an energy-efficient coffee machine with low thermal mass to allow for continuous drink preparation without interruption.

Available with the original coffee brewer or instant powder supply, both models come with an innovative touch display selection.

HS7

G-Caffè UNI-Q ESPRESSO

TECHNICAL SPECIFICATIONS	HS7
DIMENSIONS H x W x D (mm)	1830 x 650 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm Ø 78-80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	7" Touch Screen
INGREDIENT CANISTER	6x M size (4.4 l)
WATER FITTING CONNCTION	G 3/4" 2-8 bar
PROTOCOL	Executive / MDB
POWER SUPPLY	220-230 V / 50-60 Hz
POWER CONSUMPTION	134 wh/L - 692 wh/24h in Idle Mode *

* Measured at 15L/24h - 257 cups of 58ml



Uniqueness at a glimpse

Enjoy an authentic Italian espresso: G-Caffè. UNI-Q is the freestanding coffee vending machine that extracts all the essence of coffee to its utmost flavour thanks to its ingeniously designed espresso brewer.

Equipped with an innovative temperature management system with an instant heater, G-Caffè. UNI-Q is an energy-efficient coffee machine with low thermal mass to allow for continuous drink preparation without interruption.

Available with the original coffee brewer or instant powder supply, both models come with an innovative touch display selection.

HN7

G-Caffè UNI-Q INSTANT

TECHNICAL SPECIFICATIONS	HN7
DIMENSIONS H x W x D (mm)	1830 x 650 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm Ø 78-80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	7" Touch Screen
INGREDIENT CANISTER	8x M size (4.4 l)
WATER FITTING CONNCTION	G 3/4" 2-8 bar
PROTOCOL	Executive / MDB
POWER SUPPLY	220-230 V / 50-60 Hz
POWER CONSUMPTION	134 wh/L - 692 wh/24h in Idle Mode *

* Measured at 15L/24h - 257 cups of 58ml