



DM9 OD

Outdoor Refreshment

High reliability is achieved through extreme simplicity in use and maintenance. Now SandenVendo offers OUTDOOR versions of the most popular model G-Drink. Weather resistance and anti-vandalism fittings can expand your business to OUTDOOR locations!

OUTDOOR FEATURES - FRONT GLASS PROTECTION

- ROOF
- THERMAL MAGNETIC CIRCUIT BREAKER
- TEMPERATURE CONTROLLER FOR OUTDOOR
- COOLING UNIT WITH HEATER ANTIFREEZE FUNCTION (WORKS ALSO OUTSIDE TEMPERATURE BELOW ZERO)
- WATERPROOF IP34
- ANTI-VANDALISM (COIN INSERT, KEY PAD AND COIN-RETURN)
- HEATED GLASS ANTI-CONDENSATION
- AN EXCELLENT LED ILLUMINATION ALSO IN DARK

G-Drink Standard DM9 Vertical Outdoor

TECHNICAL SPECIFICATIONS

	DM9 OD
DIMENSIONS H x W x D (mm)	1875* x 1260 x 1010
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230 V / 50 Hz

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- BRANDING
- SPECIAL CODED LOCK (RIELDA)
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- BRANDING
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE



DM6 OD

Outdoor Refreshment

High reliability is achieved through extreme simplicity in use and maintenance. Now SandenVendo offers OUTDOOR versions of the most popular model G-Drink. Weather resistance and anti-vandalism fittings can expand your business to OUTDOOR locations!

OUTDOOR FEATURES - FRONT GLASS PROTECTION

- ROOF
- THERMAL MAGNETIC CIRCUIT BREAKER
- TEMPERATURE CONTROLLER FOR OUTDOOR
- COOLING UNIT WITH HEATER ANTIFREEZE FUNCTION (WORKS ALSO OUTSIDE TEMPERATURE BELOW ZERO)
- WATERPROOF IP34
- ANTI-VANDALISM (COIN INSERT, KEY PAD AND COIN-RETURN)
- HEATED GLASS ANTI-CONDENSATION
- AN EXCELLENT LED ILLUMINATION ALSO IN DARK

G-Drink Standard DM6 Vertical Outdoor

TECHNICAL SPECIFICATIONS	DM6 OD
DIMENSIONS H x W x D (mm)	1875* x 990 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230 V / 50 Hz

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL
CUSTOMIZED CABINET COLOUR
BRANDING
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
LOCK PROTECTION
BRANDING
PRODUCT SPACERS
VARIOUS FITTING KITS
SECURITY CASH BOX SYSTEM
CO2 COOLING UNIT AVAILABLE