



Essentials at your fingertips

Equipped with a vertical lift system and a highly interactive and customizable touch display, G-Drink Touch is the automatic vending machine designed to engage customers and boost your sales.

Created with the aims of a marketing tool, the top-notch touch display holds an attractive, user-friendly multi-selection feature that will persuade customers to purchase more items while providing useful nutritional insights and advertising brand promotions: an advanced control panel that enables you to effortlessly manage the vending machine.

DT6

G-Drink Touch 6 Vertical

TECHNICAL SPECIFICATIONS	DT6
DIMENSIONS H x W x D (mm)	1830* x 940 x 880
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
DISPLAY	7" Touch screen
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1330

* With adjustable leveling screw



Essentials at your fingertips

Equipped with a vertical lift system and a highly interactive and customizable touch display, G-Drink Touch is the automatic vending machine designed to engage customers and boost your sales.

Created with the aims of a marketing tool, the top-notch touch display holds an attractive, user-friendly multi-selection feature that will persuade customers to purchase more items while providing useful nutritional insights and advertising brand promotions: an advanced control panel that enables you to effortlessly manage the vending machine.

DT9

G-Drink Touch 9 Vertical

TECHNICAL SPECIFICATIONS	DT9
DIMENSIONS H x W x D (mm)	1830* x 1215 x 880
WEIGHT (NET - Standard machine without options)	345 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
DISPLAY	7" Touch screen
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1562

* With adjustable leveling screw