



## DO IT SMART, BACK-LOAD IT

Load the vending machine directly from your shop.

The smart, easy and eco-friendly solution to deliver the best of your products. Forget sudden temperature changes, reduce your workload and keep the highest hygienic standards: the new Back-Loading system is designed to ease the operations of butcher shops professionals by allowing the products loading process directly from inside the shop into the vending machine.

SBX-H2

# BACK LOADER MASTER 10

TECHNICAL SPECIFICATIONS	SBX-H2
DIMENSIONS H x W x D (mm)	1830 x 1125 x 935
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Min. 4 / Max. 6
NO. OF SELECTIONS	Max. 60
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1666 (Cat. 3)