



SMX OD

Snacking, Solved!

Europe's most successful snack machine with its stunning technical features and versatile functions is now available in an OUTDOOR version to extend your business beyond boundaries. The unit is weather resistant and vandalism proof; it assures safety and security for your business in all OUTDOOR locations.

OUTDOOR FEATURES - FRONT GLASS PROTECTION

- ROOF
- THERMAL MAGNETIC CIRCUIT BREAKER
- TEMPERATURE CONTROLLER FOR OUTDOOR
- COOLING UNIT WITH HEATER ANTIFREEZE FUNCTION (WORKS ALSO OUTSIDE TEMPERATURE BELOW ZERO)
- WATERPROOF IP34
- ANTI-VANDALISM (COIN INSERT, KEY PAD AND COIN-RETURN)
- HEATED GLASS ANTI-CONDENSATION
- AN EXCELLENT LED ILLUMINATION

ALSO IN DARK

G-Snack Standard Ten (X) Outdoor - SMX OD

TECHNICAL SPECIFICATIONS

	SMX OD
DIMENSIONS H x W x D (mm)	1875 x 1200 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	650 W
POWER SUPPLY	230 V / 50 Hz

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- VARIOUS FITTING KITS
- 7TH SHELF
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR



SM8 OD

Snacking, Solved!

Europe's most successful snack machine with its stunning technical features and versatile functions is now available in an OUTDOOR version to extend your business beyond boundaries. The unit is weather resistant and vandalism proof; it assures safety and security for your business in all OUTDOOR locations.

OUTDOOR FEATURES - FRONT GLASS PROTECTION

- ROOF
- THERMAL MAGNETIC CIRCUIT BREAKER
- TEMPERATURE CONTROLLER FOR OUTDOOR
- COOLING UNIT WITH HEATER ANTIFREEZE FUNCTION (WORKS ALSO OUTSIDE TEMPERATURE BELOW ZERO)
- WATERPROOF IP34
- ANTI-VANDALISM (COIN INSERT, KEY PAD AND COIN-RETURN)
- HEATED GLASS ANTI-CONDENSATION
- AN EXCELLENT LED ILLUMINATION

ALSO IN DARK

G-Snack Standard Eight (VIII) Outdoor - SM8 OD

TECHNICAL SPECIFICATIONS	SM8 OD
DIMENSIONS H x W x D (mm)	1875 x 1030 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL
SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
VARIOUS FITTING KITS
7TH SHELF
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR



SM6 OD

Snacking, Solved!

Europe's most successful snack machine with its stunning technical features and versatile functions is now available in an OUTDOOR version to extend your business beyond boundaries. The unit is weather resistant and vandalism proof; it assures safety and security for your business in all OUTDOOR locations.

OUTDOOR FEATURES - FRONT GLASS PROTECTION

- ROOF
- THERMAL MAGNETIC CIRCUIT BREAKER
- TEMPERATURE CONTROLLER FOR OUTDOOR
- COOLING UNIT WITH HEATER ANTIFREEZE FUNCTION (WORKS ALSO OUTSIDE TEMPERATURE BELOW ZERO)
- WATERPROOF IP34
- ANTI-VANDALISM (COIN INSERT, KEY PAD AND COIN-RETURN)
- HEATED GLASS ANTI-CONDENSATION
- AN EXCELLENT LED ILLUMINATION

ALSO IN DARK

G-Snack Standard six (VI) Outdoor - SM6 OD

TECHNICAL SPECIFICATIONS

	SM6 OD
DIMENSIONS H x W x D (mm)	1875 X 890 X 1010
WEIGHT (NET - Standard machine without options)	325 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Exécutif / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C jusqu'à +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	650 W
POWER SUPPLY	230 V / 50 Hz

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- VARIOUS FITTING KITS
- 7TH SHELF
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR