



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

STX OD

G-Snack Ten (X) Touch Outdoor

TECHNICAL SPECIFICATIONS

STX OD

DIMENSIONS H x W x D (mm)	1900 x 1200 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1553 (Cat. 2) 1836 (Cat. 3) 1714 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST8 OD

G-Snack Eight (VIII) Touch Outdoor

TECHNICAL SPECIFICATIONS

	ST8 OD
DIMENSIONS H x W x D (mm)	1900 x 1030 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 56
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1232 (Cat. 2) 1619 (Cat. 3) 1414 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
BELT SYSTEM
ROTARY SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST6 OD

G-Snack Six (VI) Touch Outdoor

TECHNICAL SPECIFICATIONS

	ST6 OD
DIMENSIONS H x W x D (mm)	1900 x 890 x 1010
WEIGHT (NET - Standard machine without options)	325 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 42
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1280 (Cat. 2) 1518 (Cat. 3) 1545 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS