



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... [\(more at our website\)](#)

TSC

CaffèUNO "PRO" Espresso

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	TSC
DIMENSIONS H x W x D (mm)	770 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	2.4 kg (hopper)
POWDER CANISTER	2 Large 1 Small
GRINDER	Professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50/60 Hz
ENERGY CONSUMPTION*	134 Wh/L

*Energy consumption in Wh per liter of espresso dispensed

OPTIONAL

TOUCH SCREEN
LARGE ESPRESSO BREWER
DOUBLE GRINDER
CUP SENSOR
WATER TANK KIT 20 LT.
WATER SOFTENER (FILTER)
SPECIAL CODED LOCK (RIELDA)
PAYMENT SYSTEM
BASE CABINET
PAYMENT TOWER MODULE
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED PANEL
CUSTOMIZED CABINET COLOUR



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... [\(more at our website\)](#)

TSE

CaffèUNO Espresso

TECHNICAL SPECIFICATIONS

TSE

OPTIONAL

DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	1.2 kg
POWDER CANISTER	2 Large 1 Small
GRINDER	Professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50/60 Hz
ENERGY CONSUMPTION*	134 Wh/L

TOUCH SCREEN
LARGE ESPRESSO BREWER
DOUBLE GRINDER
CUP SENSOR
WATER TANK KIT 20 LT.
WATER SOFTENER (FILTER)
SPECIAL CODED LOCK (RIELDA)
PAYMENT SYSTEM
BASE CABINET
PAYMENT TOWER MODULE
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED PANEL
CUSTOMIZED CABINET COLOUR

*Energy consumption in Wh per liter of espresso dispensed



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... [\(more at our website\)](#)

TSH

CaffèUNO Instant

TECHNICAL SPECIFICATIONS

TSH

OPTIONAL

DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
POWDER CANISTER	2 Large 2 Medium 1 Small
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCTION	G 3/4" 0.2-8 Bar (0.2 Mpa - 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50 /60 Hz
ENERGY CONSUMPTION*	134 Wh/L

TOUCH SCREEN
CUP SENSOR
WATER TANK KIT 20 LT.
WATER SOFTENER (FILTER)
SPECIAL CODED LOCK (RIELDA)
PAYMENT SYSTEM
PAYMENT TOWER MODULE
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED PANEL
CUSTOMIZED CABINET COLOUR

*Energy consumption in Wh per liter of espresso dispensed