



The ultimate vending bargain

The FlexStack provides unparalleled flexibility with its fully modular design. You can choose between narrow or adjustable wide stack modules, compatible with 1-liter or 1.5-liter PET bottles, available in three core configurations. The modules are easily interchangeable for added convenience. Moreover, with a strong focus on environmental sustainability, this line has been developed with the HC (R290) Hydrocarbon version, reaffirming our commitment to using natural refrigerants. Upgrade your B&C with the IP34-compliant Outdoor kit: a solution with rain protection panels and integrated drainage channels for optimal performance.

CFX-FLEX

B&C Design Flexstack 10

TECHNICAL SPECIFICATIONS

	CFX-FLEX
DIMENSIONS H x W x D (mm)	1830 x 1015 x 955
WEIGHT (NET - Standard machine without options)	375 Kg
NO. OF SELECTIONS	10
NO. OF MODULES	from 5 to 7
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +25°C
CLIMATE CLASS	N (+16°C up to +32°C)
COOLING UNIT	HCD
POWER SUPPLY	220/240 V / 50 Hz
MAX. POWER CONSUMPTION	320 W
ENERGY CLASS	B
ENERGY CONSUMPTION - kWh/annum	577

OPTIONAL

SPECIAL CODED LOCK (RIELDA)
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
DEX / UCS KIT
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR