



Your coffee break just got better

Created with the customers' needs in mind, G-Caffè UNI-Q Touch is equipped with a new, 18" touch display with a disability-friendly interface; a smart and innovative display designed to communicate with the Slave vending machine combined with the new G-Caffè UNI-Q Touch machine. Connect a G-Snack Slave machine to the new G-Caffè UNI-Q Touch and provide customers with a full array of snacks to match their hot drinks; the new 18.5" touch display will collect each multi-purchasing order and guide the users throughout the entire operation while showcasing product offers, nutrition facts and graphic contents of your choice.

HS 7T

G-Caffè UNI-Q TOUCH ESPRESSO

TECHNICAL SPECIFICATIONS

HS 7T

DIMENSIONS H x W x D (mm)	1830 x 655 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm Ø 80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	18.5" Touch Screen
INGREDIENT CANISTER	6x M size (4.4 l)
WATER FITTING CONNCTION	G 3/4" 2-8 bar (0,2 Mpa - 0,8 Mpa)
PROTOCOL	Executive / MDB
INSTANT HEATER (RATED POWER)	1x 2300W (Espresso) 1x 3200W (Powder)
POWER SUPPLY	220-240 V / 50-60 Hz
POWER CONSUMPTION	134 Wh/L

*Energy consumption in Wh per liter of Espresso dispensed

OPTIONAL

LARGE ESPRESSO BREWER
DOUBLE GRINDER
CUP SENSOR
WATER TANK KIT 20 LT.
WATER SOFTENER (FILTER)
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
TELEMETRY KIT
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION



Your coffee break just got better

Created with the customers' needs in mind, G-Caffè UNI-Q Touch is equipped with a new, 18" touch display with a disability-friendly interface; a smart and innovative display designed to communicate with the Slave vending machine combined with the new G-Caffè UNI-Q Touch machine. Connect a G-Snack Slave machine to the new G-Caffè UNI-Q Touch and provide customers with a full array of snacks to match their hot drinks; the new 18.5" touch display will collect each multi-purchasing order and guide the users throughout the entire operation while showcasing product offers, nutrition facts and graphic contents of your choice.

HN 7T

G-Caffè UNI-Q TOUCH INSTANT

TECHNICAL SPECIFICATIONS

HN 7T

DIMENSIONS H x W x D (mm)	1830 x 655 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm Ø 80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	18.5" Touch Screen
INGREDIENT CANISTER	8x M size (4.4 l)
WATER FITTING CONNCTION	G 3/4" 2-8 bar (0,2 Mpa - 0,8 Mpa)
PROTOCOL	Executive / MDB
INSTANT HEATER (RATED POWER)	1x 2300W
POWER SUPPLY	220-240 V / 50-60 Hz
POWER CONSUMPTION	134 Wh/L

*Energy consumption in Wh per liter of Espresso dispensed

OPTIONAL

CUP SENSOR
WATER TANK KIT 20 LT.
WATER SOFTENER (FILTER)
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
TELEMETRY KIT
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION