



Elevate your vending standards

Contrary to the popular belief that “standard” means “less”, our G-Drink Standard model is an automatic vending machine that leaves nothing to be desired from other models on the market. Equipped with SandenVendo's flagship cooling technologies and a vertical lift system, G-Drink Standards is available in two spacious models with 9 or 6 selections per shelf. Each model comes with a new LED illumination structure designed to enhance the visibility of the drinks displayed inside. Furthermore, our G-Drink Standard allows for dispensing glass bottles such as beer, champagne, and fresh juices at the perfect temperature.

DM9

G-Drink Standard 9 Vertical

TECHNICAL SPECIFICATIONS

	DM9
DIMENSIONS H x W x D (mm)	1830* x 1215 x 845
WEIGHT (NET - Standard machine without options)	345 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	370 W
ENERGY CLASS	C
ENERGY CONSUMPTION - kWh/annum	817

*With adjustable leveling screw

OPTIONAL

SPECIAL CODED LOCK (RIELDA)
LOCK PROTECTION
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
ROOF KIT
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR



Elevate your vending standards

Contrary to the popular belief that "standard" means "less", our G-Drink Standard model is an automatic vending machine that leaves nothing to be desired from other models on the market.

Equipped with SandenVendo's flagship cooling technologies and a vertical lift system, G-Drink Standards is available in two spacious models with 9 or 6 selections per shelf. Each model comes with a new LED illumination structure designed to enhance the visibility of the drinks displayed inside. Furthermore, our G-Drink Standard allows for dispensing glass bottles such as beer, champagne, and fresh juices at the perfect temperature.

DM6

G-Drink Standard 6 Vertical

TECHNICAL SPECIFICATIONS

	DM6
DIMENSIONS H x W x D (mm)	1830*x 940 x 845
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	370 W
ENERGY CLASS	C
ENERGY CONSUMPTION - kWh/annum	624

*With adjustable leveling screw

OPTIONAL

SPECIAL CODED LOCK (RIELDA)
LOCK PROTECTION
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
ROOF KIT
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR