



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG9

## G-Drink 9 Vendo Legend®

TECHNICAL SPECIFICATIONS	DG9
DIMENSIONS H x W x D (mm)	1830*x 1220 x 845
WEIGHT (NET - Standard machine without options)	345 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	370 W
ENERGY CLASS	TBC
ENERGY CONSUMPTION - kWh/annum	TBC

\*With adjustable leveling screw



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG6

## G-Drink 6 Vendo Legend®

TECHNICAL SPECIFICATIONS	DG6
DIMENSIONS H x W x D (mm)	1830*x 945 x 845
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	370 W
ENERGY CLASS	TBC
ENERGY CONSUMPTION - kWh/annum	TBC

\*With adjustable leveling screw