



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG9

G-Drink 9 Vendo Legend®

	DG9
ALTO x ANCHO x FONDO (mm)	1830*x 1220 x 845
PESO (NETO estándar sin opciones)	345 kg
Nº DE SELECCIONES POR BANDEJA	9
Nº DE BANDEJAS	Estándar 5 / Máx. 7
Nº DE SELECCIONES	Estándar 45 / Máx. 63
CAPACIDAD MÁX. (LATAS 330 ml)	504
CAPACIDAD MÁX. (BOTELLAS PET 500 ml)	360
PROTOCOLO	Executive / MDB
CONTROL SISTEMA DE REFRIGERACIÓN	Electrónico
TEMPERATURA INTERNA	+2°C hasta +10°C
SISTEMA DE REFRIGERACIÓN	HCD
SUMINISTRO ELÉCTRICO	230/240 V - 50/60 Hz
MÁXIMO CONSUMO ENERGÉTICO	370 W
CLASE DE ENERGIA	TBC
CONSUMO ENERGÉTICO - kWh/annum	TBC

*Con patas regulables



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG6

G-Drink 6 Vendo Legend®

	DG6
ALTO x ANCHO x FONDO (mm)	1830*x 945 x 845
PESO (NETO estándar sin opciones)	295 kg
Nº DE SELECCIONES POR BANDEJA	6
Nº DE BANDEJAS	Estándar 5 / Máx. 7
Nº DE SELECCIONES	Estándar 30 / Máx. 42
CAPACIDAD MÁX. (LATAS 330 ml)	336
CAPACIDAD MÁX. (BOTELLAS PET 500 ml)	240
PROTOCOLO	Executive / MDB
CONTROL SISTEMA DE REFRIGERACIÓN	Electrónico
TEMPERATURA INTERNA	+2°C hasta +10°C
SISTEMA DE REFRIGERACIÓN	HCD
SUMINISTRO ELÉCTRICO	230/240 V - 50/60 Hz
MÁXIMO CONSUMO ENERGÉTICO	370 W
CLASE DE ENERGIA	TBC
CONSUMO ENERGÉTICO - kWh/annum	TBC

*Con patas regulables