



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG9

G-Drink 9 Vendo Legend®

	DG9
DIMENSIONS H x L x P (mm)	1830*x 1220 x 845
POIDS (Net - Machine standard sans option)	340 kg
NOMBRE DE SÉLECTION PAR PLATEAU	9
NOMBRE DE PLATEAU	Standard 5 / Max. 7
NOMBRE DE SÉLECTION	Standard 45 / Max. 63
CAPACITÉ MAXI (CANETTES DE 0,33 L)	504
CAPACITÉ MAXI (BOUTEILLES PET DE 0,50 L)	360
PROTOCOLE	Exécutif / MDB
CONTRÔLE DU SYSTÈME DE REFROIDISSEMENT	Électronique
TEMPÉRATURE INTERNE	+2°C jusqu'à +10°C
UNITÉ RÉFRIGÉRANTE	HCD
ALIMENTATION ÉLECTRIQUE	230/240 V - 50/60 Hz
CONSOMMATION D'ÉNERGIE MAX.	370 W
CLASSE ÉNERGÉTIQUE	TBC
CONSOMMATION ÉNERGÉTIQUE - kWh/annum	TBC

*Avec pieds réglables



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG6

G-Drink 6 Vendo Legend®

	DG6
DIMENSIONS H x L x P (mm)	1830*x 945 x 845
POIDS (Net - Machine standard sans option)	295 Kg
NOMBRE DE SÉLECTION PAR PLATEAU	6
NOMBRE DE PLATEAU	Standard 5 / Max. 7
NOMBRE DE SÉLECTION	Standard 30 / Max. 42
CAPACITÉ MAXI (CANETTES DE 0,33 L)	336
CAPACITÉ MAXI (BOUTEILLES PET DE 0,50 L)	240
PROTOCOLE	Exécutif / MDB
CONTRÔLE DU SYSTÈME DE REFROIDISSEMENT	Électronique
TEMPÉRATURE INTERNE	+2°C jusqu'à +10°C
UNITÉ RÉFRIGÉRANTE	HCD
ALIMENTATION ÉLECTRIQUE**	230/240 V - 50/60 Hz
CONSOMMATION D'ÉNERGIE MAX.	370 W
CLASSE ÉNERGÉTIQUE	TBC
CONSOMMATION ÉNERGÉTIQUE - kWh/annum	TBC

*Avec pieds réglables