



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

STX OD

G-Snack Ten (X) Touch Outdoor

	STX OD
AFMETINGEN H x B x D (mm)	1900 x 1200 x 1010
GEWICHT (NETTO: standaard zonder opties)	400 kg
AANTAL SELECTIES PER PLATEAU	10
AANTAL PLATEAUS	Standaard 6 / Max. 7
AANTAL SELECTIES	Max. 70
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
TEMPERATUURCONTROLE	Elektronisch
INTERN TEMPERATUURBEREIK	+2°C tot +18°C
OMGEVINGSTEMPERATUUR	-15°C tot +38°C
KOEL SYSTEEM	HCD
ELEKTRISCHE VOEDING	230/240 V - 50/60 Hz
MAX. VERBRUIK	450 W
ENERGIEKLASSE	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGIEVERBRUIK - kWh/annum	1553 (Cat. 2) 1836 (Cat. 3) 1714 (Cat. 4)

OPTIONAL

SNELLE LIFT
E- LABELING ELECTRONISCHE ETIKETERING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
GEMOTORISEERD SLOT VOOR UITGAVE LUIK
SLOT RIELDA MET SPECIAL ECODE
AFSLUITBARE GELDKASSA
MUUR/VLOER BEVESTIGINGSKIT
MUNTPROEVER
KIT EVA DTS
VERSCHILLENDE MONTAGE KITS



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST8 OD

G-Snack Eight (VIII) Touch Outdoor

	ST8 OD
AFMETINGEN H x B x D (mm)	1900 x 1030 x 1010
GEWICHT (NETTO: standaard zonder opties)	350 kg
AANTAL SELECTIES PER PLATEAU	8
AANTAL PLATEAUS	Standaard 6 / Max. 7
AANTAL SELECTIES	Max. 56
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
TEMPERATUURCONTROLE	Elektronisch
INTERN TEMPERATUURBEREIK	+2°C tot +18°C
OMGEVINGSTEMPERATUUR	-15°C tot +38°C
KOEL SYSTEEM	HCD
ELEKTRISCHE VOEDING	230/240 V - 50/60 Hz
MAX. VERBRUIK	450 W
ENERGIEKLASSE	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGIEVERBRUIK - kWh/annum	1232 (Cat. 2) 1619 (Cat. 3) 1414 (Cat. 4)

OPTIONAL

SNELLE LIFT
E- LABELING ELECTRONISCHE ETIKETERING
BELT SYSTEM
ROTARY SYSTEM
KIT SANDWICH
KIT BAGUETTE
GEMOTORISEERD SLOT VOOR UITGAVE LUIK
SLOT RIELDA MET SPECIAL ECODE
AFSLUITBARE GELDKASSA
MUUR/VLOER BEVESTIGINGSKIT
MUNTPROEVER
KIT EVA DTS
VERSCHILLENDE MONTAGE KITS



Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST6 OD

G-Snack Six (VI) Touch Outdoor

	ST6 OD
AFMETINGEN H x B x D (mm)	1900 x 890 x 1010
GEWICHT (NETTO: standaard zonder opties)	325 kg
AANTAL SELECTIES PER PLATEAU	6
AANTAL PLATEAUS	Standaard 6 / Max. 7
AANTAL SELECTIES	Max. 42
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
TEMPERATUURCONTROLE	Elektronisch
INTERN TEMPERATUURBEREIK	+2°C tot +18°C
OMGEVINGSTEMPERATUUR	-15°C tot +38°C
KOEL SYSTEEM	HCD
ELEKTRISCHE VOEDING	230/240 V - 50/60 Hz
MAX. VERBRUIK	450 W
ENERGIEKLASSE	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGIEVERBRUIK - kWh/annum	1280 (Cat. 2) 1518 (Cat. 3) 1545 (Cat. 4)

OPTIONAL

SNELLE LIFT
E- LABELING ELECTRONISCHE ETIKETERING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
GEMOTORISEERD SLOT VOOR UITGAVE LUIK
SLOT RIELDA MET SPECIAL ECODE
AFSLUITBARE GELDKASSA
MUUR/VLOER BEVESTIGINGSKIT
MUNTPROEVER
KIT EVA DTS
VERSCHILLENDE MONTAGE KITS