



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG9

G-Drink 9 Vendo Legend®

	DG9
AFMETINGEN H x B x D (mm)	1830*x 1220 x 845
GEWICHT (NETTO: standaard zonder opties)	340 kg
AANTAL SELECTIES PER PLATEAU	9
AANTAL PLATEAUS	Standaard 5 / Max. 7
AANTAL SELECTIES	Standaard 45 / Max. 63
MAX. CAPACITEIT (0,33 l BLIKKEN)	504
MAX. CAPACITEIT (0,50 l PET FLESSEN)	360
PROTOCOL	Executive / MDB
TEMPERATUURCONTROLE	Elektronisch
INTERN TEMPERATUURBEREIK	+2°C tot +10°C
KOEL SYSTEEM	HCD
ELEKTRISCHE VOEDING	230/240 V - 50/60 Hz
MAX. VERBRUIK	370 W
ENERGIEKLASSE	TBC
ENERGIEVERBRUIK - kWh/annum	TBC

*Met regelbare voet



A new premium range by SandenVendo inspired by the timeless heritage of Vendo.

For almost 90 years, Vendo has shaped the world of automatic retail, combining engineering excellence with distinctive design. Today, we proudly introduce its Vendo Legend®, a premium vending line that revives the iconic spirit of Vendo's golden era while embracing the technology and sustainability of modern vending. The Vendo Legend® Line reinterprets the aesthetic language of the 1950s and 1960s through contemporary engineering, creating a vending machine that is not only functional, but a true design statement.

DG6

G-Drink 6 Vendo Legend®

	DG6
AFMETINGEN H x B x D (mm)	1830*x 945 x 845
GEWICHT (NETTO: standaard zonder opties)	295 kg
AANTAL SELECTIES PER PATEAU	6
AANTAL PATEAUS	Standaard 5 / Max. 7
AANTAL SELECTIES	Standaard 30 / Max. 42
MAX. CAPACITEIT (0,33 l BLIKKEN)	336
MAX. CAPACITEIT (0,50 l PET FLESSEN)	240
PROTOCOL	Executive / MDB
TEMPERATUURCONTROLE	Elektronisch
INTERN TEMPERATUURBEREIK	+2°C tot +10°C
KOEL SYSTEEM	HCD
ELEKTRISCHE VOEDING	230/240 V - 50/60 Hz
MAX. VERBRUIK	370 W
ENERGIEKLASSE	TBC
ENERGIEVERBRUIK - kWh/annum	TBC

*Met regelbare voet